


TALYST®




AUTOLABEL: Barcode Labeling Software

Specification Sheet

AutoLabel® by Talyst utilizes unique software that allows you to customize your labels including color, ensuring virtually 100% of your medications have a scan-ready bar code and a human-readable label.



[front view]



[side view]

AUTOLABEL DIMENSIONS

(Black & white Printer)

- Width:** 10.8" (275mm)
- Depth:** 19.0" (483mm)
- Height:** 9.4" (239mm)
- Weight:** 28.4lbs (12.88kg)

NOTE: The complete AutoLabel system includes two printers. These components must be placed on flat surfaces capable of supporting 150 lbs minimum. For color-coded labels, different specifications are needed. Please contact Talyst at, 877.4.TALYST, for more details.

AUTOLABEL: Specifications

AutoLabel® by Talyst is a complete barcoding solution that provides color-coded barcode and standard black & white transfer labels to improve patient safety. Nurse-friendly labels ensure a consistent, readable barcode makes it to the bedside for scanning.

Its flexible interface allows you to:

- NDDF Drug Database by Gold Standard Drug Databases
- Create any size custom sheet labels
- Part linear & 2-D bar codes
- On-screen pharmacist approval
- 1-2-3 scan-and-print technology
- Print drug images in color
- Use with any labels from any vendor
- Windows 7 Compatible (32 & 64 bit)

OPERATION

Environmental Operating Temperature: +5°C to +40°C (+41°F to +104°F)
Humidity 10 to 90%, non-condensing

Display: Back-lit LCD and 3 LED indicators

Keypad: Alpha-numeric keypad

Graphics: Supports PCX file format

Interfaces: EasyLAN 10/100BaseT internal Ethernet RS-232, up to 115.2 kB/s, USB 2.0

CONSUMABLES

Maximum Print Width: 112mm (4.41 in)

Media Thickness: 60 to 170µm
(2.4 to 6.7 mil)

Barcode Flag Labels: 200-00101-00
(2 rolls/case)

Barcode Circle Labels: 200-00401-00
(9 rolls/case)

Barcode Flag Ribbons: 200-00102-00
(6 rolls/case)

Barcode Circle Ribbons: 200-00402-00
(3 rolls/case)

Usage Ratio: 1 ribbon roll per 3 label rolls

MINIMUM SPACE REQUIRED PER UNIT

Width: 20"	Depth: 24"	Counter Height: 32"
-------------------	-------------------	----------------------------

SOFTWARE

Operating System: Windows® 7 compatible. Compatible with 32 and 64-bit installations of Windows® 7.

POWER

Main Power: 115 VAC, 10A, 50/60Hz; 115/230VAC Auto-Switch with Power Factor Correction

Supplied Power Cord: IEC C13 to NEMA 5-15 (F)

SCANNER SPECIFICATIONS

Dimensions (LxWxH): 4.1" x 2.8" x 6.3"

Scan Pattern: Area Image
(838 x 640 pixel array)

Motion Tolerance: Up to 240 in/s for 13 mil UPC at optimal focus

Decode Capability: Reads standard 1D, PDF, 2D, Postal and OCR symbologies

COMPLIANCE

CE (EN55022 Class A), FCC Class A, UL, CSA, C-Tick

Supported Symbologies:

One-dimensional Codes: Codabar, Code 11, Code 39, Code 93, MSI(modified Plessey), Code 128, Code 128 Subset A-C, DUN-14/16, UPC/EAN Codes (EAN 8, EAN 13, UPC Version A, UPC Version E), EAN-128, EAN-128 Subset A-C*, Industrial 2 of 5, Interleaved 2 of 5, Interleaved 2 of 5 A, Matrix 2 of 5*, ISBT 128, Planet, Postnet, Straight 2 of 5*, UCC-128 Serial Shipping Container Code, RSS, HIBC Code 39, HIBC Code 128, JIS-ITF
Two-dimensional Codes: Aztec, Code 16K, Code 49, Data Matrix, MaxiCode, PDF417, QR Code, Micro PDF417, EAN.UCC Composite